

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 01.07.2011

Replaces: 17.06.2010

Ref: 0009.8.A/DR

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** TECTANE Paint And Gasket Stripper
- **Article number:** 1180001
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** *Paint remover*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SIROFLEX LIMITED
Dodworth Business Park, Dodworth,
Barnsley, South Yorkshire, S75 3SP
-
- Tel: 01226 771600*
Fax: 01226 771601
- **Further information obtainable from:**
info@siroflex.co.uk
www.siroflex.co.uk
-
- **Emergency telephone number:** *Tel: +49 (0)9366/9071-26 Monday to Thursday 7:15 to 18:00 CET*

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Date: 01.07.2011

Replaces: 17.06.2010

Ref: 0009.8.A/DR

Trade name: TECTANE Paint And Gasket Stripper

(Contd. of page 1)

· Code letter and hazard designation of product:



Xi Irritant
F+ Extremely flammable

· Risk phrases:

- 12 Extremely flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe spray.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.
- 56 Dispose of this material and its container to hazardous or special waste collection point.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

· Classification in accordance with Directive 75/324/EEC: Extremely flammable

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether F+ R12 Flam. Gas 1, H220; Press. Gas, H280	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R10-66-67 Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
CAS: 872-50-4 EINECS: 212-828-1	N-methyl-2-pyrrolidone Xi R36/38 Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol R10-67 Flam. Liq. 3, H226	2.5-10%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 01.07.2011

Replaces: 17.06.2010

Ref: 0009.8.A/DR

Trade name: TECTANE Paint And Gasket Stripper

(Contd. of page 2)

CAS: 112-34-5 EINECS: 203-961-6	2-(2-butoxyethoxy)ethanol ☒ Xi R36 ⚠ Eye Irrit. 2, H319	2.5-10%
CAS: 108-94-1 EINECS: 203-631-1	cyclohexanone ☒ Xn R20 R10 ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332	2.5-10%

· **Regulation (EC) No 648/2004 on detergents / Labelling for contents**

non-ionic surfactants

< 5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

Carbon dioxide

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

· **Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 01.07.2011

Replaces: 17.06.2010

Ref: 0009.8.A/DR

Trade name: **TECTANE Paint And Gasket Stripper**

(Contd. of page 3)

· **Reference to other sections** See Section 13 for disposal information.

7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:** Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.· **Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****115-10-6 dimethyl ether**WEL Short-term value: 958 mg/m³, 500 ppmLong-term value: 766 mg/m³, 400 ppm**67-64-1 acetone**WEL Short-term value: 3620 mg/m³, 1500 ppmLong-term value: 1210 mg/m³, 500 ppm**123-86-4 n-butyl acetate**WEL Short-term value: 966 mg/m³, 200 ppmLong-term value: 724 mg/m³, 150 ppm**872-50-4 N-methyl-2-pyrrolidone**WEL Short-term value: 309 mg/m³, 75 ppmLong-term value: 103 mg/m³, 25 ppm

Sk

108-94-1 cyclohexanone

WEL Short-term value: 20 ppm

Long-term value: 10 ppm

Sk

· **Additional information:** The lists valid during the making were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Date: 01.07.2011

Replaces: 17.06.2010

Ref: 0009.8.A/DR

Trade name: TECTANE Paint And Gasket Stripper

(Contd. of page 4)

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Recommended filter device for short term use:** Filter AX

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

≥ 10 min

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Pink

· **Odour:** Acetone-like

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Ignition temperature:** $> 200^{\circ}\text{C}$

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Density at 20°C:** 0.76766 g/cm³

· **Solubility in / Miscibility with**

water: Not miscible or difficult to mix.

Organic solvents: 96.4 %

10 Stability and reactivity

· **Reactivity**

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 01.07.2011

Replaces: 17.06.2010

Ref: 0009.8.A/DR

Trade name: TECTANE Paint And Gasket Stripper

(Contd. of page 5)

· **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Vapours have narcotic effect.

12 Ecological information

· **Toxicity**· **Acquatic toxicity:** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

13 Disposal considerations

· **Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

16 05 04	gases in pressure containers (including halons) containing dangerous substances
15 01 04	metallic packaging

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**· **ADR/RID class:** 2 5F Gases.· **Danger code (Kemler):** -· **UN-Number:** 1950· **Packaging group:** -· **Hazard label:** 2.1

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 01.07.2011

Replaces: 17.06.2010

Ref: 0009.8.A/DR

Trade name: TECTANE Paint And Gasket Stripper

(Contd. of page 6)

- **UN proper shipping name:** 1950 AEROSOLS
- **Limited quantities (LQ)** LQ2
- **Transport category** 2
- **Tunnel restriction code** D

· **Maritime transport IMDG:**

- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**

- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

- **UN "Model Regulation":** UN1950, AEROSOLS, 2.1
- **Special precautions for user** Warning: Gases.

15 Regulatory information

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20 Harmful by inhalation.
- R36 Irritating to eyes.
- R36/38 Irritating to eyes and skin.
- R66 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 01.07.2011

Replaces: 17.06.2010

Ref: 0009.8.A/DR

Trade name: TECTANE Paint And Gasket Stripper

(Contd. of page 7)

R67 Vapours may cause drowsiness and dizziness.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

*** Data compared to the previous version altered.**

GB