

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Date: 21.07.2009

Replaces: 30.07.2008

Ref: 0007.6.A/DR

Page 1 of 6

### 1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** TECTANE White Grease
- **Article number:** 1710001
- **Application of the substance / the preparation** Lubricant
- **Manufacturer/Supplier:**  
Siroflex Limited  
Dodworth Business Park, Dodworth,  
Barnsley, South Yorkshire, England, S75 3SP  
Tel.: 01226 771600  
Fax.: 01226 771601  
info@siroflex.co.uk
- **Further information obtainable from:**  
www.siroflex.co.uk

### 2 Hazards identification

· **Hazard description:**



*Xi* Irritant

*F+* Extremely flammable

*N* Dangerous for the environment

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### 3 Composition/information on ingredients

· **Chemical characterization**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light <i>Xn</i> , <i>Xi</i> , <i>F</i> , <i>N</i> ; R 11-38-51/53-65-67	25-50%
CAS: 75-28-5 EINECS: 200-857-2	isobutane <i>F+</i> ; R 12	10-25%
CAS: 74-98-6 EINECS: 200-827-9	propane <i>F+</i> ; R 12	10-25%
CAS: 106-97-8 EINECS: 203-448-7	butane <i>F+</i> ; R 12	2.5-10%

(Contd. on page 2)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Date: 21.07.2009

Replaces: 30.07.2008

Ref: 0007.6.A/DR

Page 2 of 6

**Trade name: TECTANE White Grease**

(Contd. of page 1)

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- **After inhalation:**  
Supply fresh air; consult doctor in case of complaints.  
Take affected persons into fresh air and keep quiet.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
Immediately remove any clothing soiled by the product.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

#### 5 Fire-fighting measures

- **Suitable extinguishing agents:**  
Foam  
Fire-extinguishing powder  
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards caused by the substance, its products of combustion or resulting gases:**  
Can form explosive gas-air mixtures.  
Formation of toxic gases is possible during heating or in case of fire.
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**  
Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### 6 Accidental release measures

- **Person-related safety precautions:**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Keep away from ignition sources.
- **Measures for environmental protection:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **Additional information:** See Section 13 for disposal information.

#### 7 Handling and storage

- **Handling:**
- **Information for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**  
Protect against electrostatic charges.  
Keep ignition sources away - Do not smoke.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 3)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Date: 21.07.2009

Replaces: 30.07.2008

Ref: 0007.6.A/DR

Page 3 of 6

**Trade name: TECTANE White Grease**

(Contd. of page 2)

Do not spray onto a naked flame or any incandescent material.

- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

### 106-97-8 butane

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Recommended filter device for short term use:** Filter AX
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**  
Nitrile rubber, NBR  
Recommended thickness of the material:  $\geq 0.45$  mm
- **Penetration time of glove material**  $\geq 240$  min
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

## 9 Physical and chemical properties

- **General Information**

<b>Form:</b>	Aerosol
<b>Colour:</b>	White
<b>Odour:</b>	Petrol-like

- **Change in condition**  
**Melting point/Melting range:** Undetermined.

(Contd. on page 4)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Date: 21.07.2009

Replaces: 30.07.2008

Ref: 0007.6.A/DR

Page 4 of 6

**Trade name: TECTANE White Grease**

(Contd. of page 3)

<b>Boiling point/Boiling range:</b>	Not applicable, as aerosol.
<b>Flash point:</b>	Not applicable, as aerosol.
<b>Ignition temperature:</b>	>200°C
<b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Density at 20°C:</b>	0.67107 g/cm <sup>3</sup>
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Organic solvents:</b>	73.9 %

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>5 mg/l (rat)
------------	----------	---------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Vapours have narcotic effect.

### 12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

GB

(Contd. on page 5)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Date: 21.07.2009

Replaces: 30.07.2008

Ref: 0007.6.A/DR

Page 5 of 6

**Trade name: TECTANE White Grease**

(Contd. of page 4)

### 13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

16 05 04	gases in pressure containers (including halons) containing dangerous substances
----------	---

15 01 04	metallic packaging
----------	--------------------

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· **Land transport ADR/RID (cross-border)**



· **ADR/RID class:** 2 5F Gases.

· **Danger code (Kemler):** 23

· **UN-Number:** 1950

· **Packaging group:** -

· **Hazard label:** 2.1

· **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



· **IMDG Class:** 2.1

· **UN Number:** 1950

· **Label:** 2.1

· **Packaging group:** -

· **EMS Number:** F-D,S-U

· **Marine pollutant:** No

· **Proper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 2.1

· **UN/ID Number:** 1950

· **Label:** 2.1

· **Packaging group:** -

· **Proper shipping name:** AEROSOLS, flammable

GB

(Contd. on page 6)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Date: 21.07.2009

Replaces: 30.07.2008

Ref: 0007.6.A/DR

Page 6 of 6

**Trade name: TECTANE White Grease**

(Contd. of page 5)

### 15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



*Xi* Irritant

*F+* Extremely flammable

*N* Dangerous for the environment

· **Risk phrases:**

12 Extremely flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

23 Do not breathe aerosol.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

11 Highly flammable.

12 Extremely flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.