

## TECHNICAL DATA SHEET

### SX SILICONE SPRAY

An instant high gloss spray that can be used in a multitude of applications such as an oil, fat and solvent free lubricant, a protective and parting agent as well as a conditioner for plastics, wood, rubber and metals. Can be used safely in food preparation areas. It is a clean lubricating film that is non hardening and resistant to high temperatures. This product protects from oxidation and corrosion, has good electrical resistance and is water-repellent and antistatic.

#### USES

**Release/Antistick agent;** in plastic injection moulding, fibre glass moulding, footwear industry, ceramic ware production, rubber articles and oven shelves not in excess of +315°C.

**Instant Spray Gloss Applications;** on PVC, upholstery, rubber and plastic trims, wood and metal surfaces and an ideal renovator for car dashboards and vinyl trim.

**Lubrication;** for most plastic and synthetic/natural rubber or plastic bearing, textiles and fibres.

**PACKAGING:** 400ml aerosol packed 1 x 12

#### PREPARATION

Surfaces must be clean dry and grease free. Shake the can vigorously.

#### APPLICATION

Hold can upright, approximately 20cm from the surface. Spray lightly over the surface to achieve the required level of finish. Rub with a soft cloth and repeat this operation as required. Do not spray directly onto hot surfaces.

#### FINISHING

Remove any excess or spilled silicone spray with a dry cloth and wash area with plenty of soapy water. It is the user's responsibility to dispose of all packaging correctly.

DODWORTH BUSINESS PARK  
DODWORTH BARNSELY  
SOUTH YORKSHIRE S75 3SP

TELEPHONE: 01226 771600  
FACSIMILE: 01226 771601  
e-mail [info@siroflex.co.uk](mailto:info@siroflex.co.uk)  
[www.siroflex.co.uk](http://www.siroflex.co.uk)

Registered in England No. 2831699  
*Member of the Den Braven Sealant Group of Companies*

## **SX SILICONE SPRAY TECHNICAL DATA SHEET CONTINUED**

### **HEALTH & SAFETY**

#### **EXTREMELY FLAMMABLE**

Contains Aliphatic Hydrocarbon.

Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Keep container in a well-ventilated place. Keep away from sources of ignition. Use only in well-ventilated areas. This material and its container must be disposed of as hazardous waste.

### **STORAGE**

Store upright in well ventilated areas only. Storage temperature should never exceed 50°C. Shelf Life 12 months.

### **LIABILITY**

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.