

TECHNICAL DATA SHEET

ZWALUW SILI-KILL (SILICONE REMOVER)

Zwaluw Sili-Kill is a ready for use paste to remove the residue of cured silicone sealant.

COLOUR: Colourless

PACKING: 100ml pot

PREPARATION

Cut the silicone sealant away as far as possible with a sharp knife. Shake before use.

APPLICATION

Apply the paste thickly on the cured silicone sealant residue. After 20 - 30 minutes the sealant residue can be easily removed with a putty knife or a wooden spatula for vulnerable substrates. If necessary repeat the treatment.

FINISHING

Wash with soap and water and leave to dry.

HEALTH & SAFETY

IRRITANT

Flammable. Irritating to eyes and skin. Vapours may cause drowsiness and dizziness. Keep out of reach of children. Avoid contact with eyes. If swallowed seek medical advice immediately and show this container or label. Dispose of empty packaging correctly.

Page 1 of 2

DODWORTH BUSINESS PARK DODWORTH BARNSLEY SOUTH YORKSHIRE S75 3SP

TELEPHONE: 01226 771600 FACSIMILE: 01226 771601 e-mail info@siroflex.co.uk www.siroflex.co.uk



ZWALUW SILI-KILL TECHNICAL DATA SHEET CONTINUED

LIMITATIONS

Not recommended for thick layers. Always test a small area before use. It is the users responsibility to determine suitability.

TECHNICAL DATA	DIMENSION	SILI-KILL TECHNICAL DATA
Basis		solvent
Dwell time	min	20 - 30
Density	g/ml	0.8
Consistency		paste
Odour		weak
Frost resistant during transport till tot –15°C		yes
Shelf life between +5°C and +25°C	months	24

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.